

SP530 Bluetooth Pinpad

SP530 Bluetooth Pinpad supports IOS/Android connection to pair your existing smart phone, tablets or PDA for mobile payments. It offers the latest PCI PTS V4.0 security, EMV Level 1 & 2, EMV Contactless L1 certification which brings high security and reliable performance to process a variety of transactions.

Features and Benefits

- » Ergonomic and compact design
- » Magnetic card and EMV chip card reading & PIN entry for mobile payment
- » Optional contactless NFC reader certified with MasterCard Paypass and Visa PayWave
- » Flexible Platform supports IOS/Android connectivity via Bluetooth or USB cable
- » High-resolution display with icon and white LED backlight and icon
- » Simple, user friendly operation to pair with any mobile payment application running on existing Smartphone, Tablet or PDA
- » Ideal for any larger or small retailers to accept mobile payment reliably
- » Replaceable battery, no need to send the unit back to service center for battery replacement

| Specification | |
|-------------------------|--|
| CPU | ARM Cortex secure CPU |
| Memory | Up to 16MB flash |
| Display | 128 x 64 dots FSTN LCD with white LED Back light |
| MSR | Magnetic stripe card reader (ISO 1&2&3 track) |
| IC Card Reader | 1 x SAM sockets (optional) |
| Contactless Card Reader | Contactless reader for ISO 14443A/B, ISO18092 (optional) |
| SAM | 1 x SAM sockets (optional) |
| Realtime Clock | Lithium backed (CPU built-in) |
| Keypad | 16 keys (10 alphanumeric keys + 6 functional keys) |
| Buzzer | A single tone beeper |
| Interfaces | USB 2.0 device Port full speed (micro-usb) Bluetooth module Class 2 dual mode BLE V4.0 and EDR V3.0 (optional) Micro SD interface (optional) |
| Cable Connection | USB-toUSB (optional) |
| Battery | 480mAh Li-Polmer battery |
| Power Input | DC 5V +/- 5% (from USB cable) or Li-Polymer batter alone |
| Others | Support iOS/Android connection via Bluetooth |
| Cerfication | PCI PTS V4.0, PCI OP, PCI SRED, EMV contact L1&L2, EMV contactless L1, MasterCard PayPass, Visa PayWave, CE, FCC, Visa Ready |
| Dimension & Weight | |
| Dimension | Overall size: 110(L) x 70(W) x 19(H)mm |
| Weight | 140g |
| Operating Environment | |
| Temperature | 0-45°C |
| R.H. | 0-85% non-condense |

